



	Small Enterprise	Medium Enterprise	Large Enterprise	
Model	MC1550	MC3200	MC4200	MC6000
Access Points Supported	50	200	500	5,000
Clients Supported	1,000	2,000	5,000	50,000
Ethernet Ports	2 x 10/100/1000BASE-T (RJ45)	4 x 10/100/1000BASE-T (RJ45)	4 x 10/100/1000BASE-T (RJ45) or 2 x 10-GbE only SFP+ or 2 x 1-GbE/10-GbE SFP+	6 x 10-GbE only SFP+ or 6 x 1-GbE/10-GbE SFP+ per blade; maximum 10 blades per chassis
Mounting	Desktop Mount or 1U rack mount	1U rack mount	1U rack mount	7U rack mount
Virtual Controller Option	✓	✓	✓	-
Encryption	WEP, TKIP, DES, AES			
Authentication	WPA-Enterprise, WPA-PSK, WPA2-Enterprise, WPA2-PSK, 802.1X, MAC address, captive portal			

Meru Networks | Copyright © 2013 Meru Networks, Inc. All rights reserved worldwide. Meru Networks is a registered trademark of Meru Networks, Inc. All other trademarks, trade names, or service marks mentioned in this document are the property of their respective owners. Meru Networks assumes no responsibility for any inaccuracies in this document. Meru Networks reserves the right to change, modify, transfer, or otherwise revise this publication without notice. 05.21PCC1004.US

Email: meruinfo@merunetworks.com